



MBI

MARSH EXCAVATOR

ME-271444



CAPACITIES

Gross Weight: 155,000 lbs.
Net Weight: 80,000 lbs.
Maximum Payload: 75,000 lbs.

GROUND PRESSURE

1.5 to 2.5 lbs. per square inch

SPEED

Land: 2.0 mph
Water: 1.0 mph

OVERALL DIMENSIONS

42' 8" long x 22' wide x 6'-10" high (undercarriage only).

HYDRAULIC MOTORS AND DRIVE LINE

(2) Sauer Sundstrand Variable displacement motors driven through a planetary speed reducer.

TRAVEL OPERATION

Hydraulic power is routed from the Excavator's track drive port to the amphibious track drive motors. Steering is obtained by the existing control levers located inside the Excavator's operator cab.

PONTOONS

(2) 40' long x 7' wide x 6' high and constructed of high tensile alloy steel with 4 track chain runners per pontoon.

TRACK SYSTEM

(4) Chain strands per side of 5" pitch heavy duty marsh buggy chain connected to extra heavy duty forged 3.5" aluminum alloy track cleats with (3) U.H.M.W. wear pads per pontoon

FEATURES

- Four strand track chain, stronger system and longer track life
- Disassembles into three pieces for ease of transporting and shipping
- Hydrostatic-driven track system with braking capabilities
- Extra high flotation, giving more versatility and safer water operation

WWW.MARSHBUGGIES.COM | INFO@MARSHBUGGIES.COM

2018 Engineers Road | Belle Chasse, LA 70037 | P.O. Box 814 • Harvey, LA 70059 | 504.394.5050 | 800.264.6868 | FAX: 504.394.-5052